






D-Sluiting met moerbout Type G-2150



G-2150														
Type	Veilige werklust t	Art.nr.	Gewicht kg/st	Afmetingen mm										Tolerantie +/-
				A	B	D	F	G	K	M	P	R	G	A
1/4	0,5	7011019466	.06	11.9	7.85	6.35	15.5	19.1	40.4	24.6	39.6	6.35	1.50	1.50
5/16	0,75	7011019468	.10	13.5	9.65	7.85	19.1	25.4	48.5	29.5	46.2	7.85	1.50	1.50
3/8	1	7011019470	.15	16.8	11.2	9.65	23.1	31.0	58.5	35.8	55.0	9.365	3.30	1.50
7/16	1,5	7011019471	.22	19.1	12.7	11.2	26.9	36.1	67.5	41.1	63.5	11.2	3.30	1.50
1/2	2	7011019472	.34	20.6	16.0	12.7	30.2	41.4	77.0	46.0	71.0	12.7	3.30	1.50
5/8	3,25	7011019490	.67	26.9	19.1	16.0	38.1	51.0	95.5	58.5	89.5	16.0	3.30	1.50
3/4	4,75	7011019515	1.14	31.8	22.4	19.1	46.0	60.5	115	70.0	103	20.6	6.35	1.50
7/8	6,5	7011019533	1.74	36.6	25.4	22.4	53.0	71.5	135	81.0	120	24.6	6.35	1.50
1	8,5	7011019551	2.52	42.9	28.7	25.4	60.5	81.0	151	93.5	135	25.4	6.35	1.50
1-1/8	9,5	7011019579	3.45	46.0	31.8	28.7	68.5	91.0	172	103	150	31.8	6.35	1.50
1-1/4	12	7011019597	4.90	51.5	35.1	31.8	76.0	100	191	115	165	35.1	6.35	1.50
1-3/8	13,5	7011019613	6.24	57.0	38.1	35.1	84.0	111	210	127	183	38.1	6.35	3.30
1-1/2	17	7011019631	8.39	60.5	41.4	38.1	92.0	122	230	137	196	41.1	6.35	3.30
1-3/4	25	7011019659	14.2	73.0	51.0	44.5	106	146	279	162	230	54.0	6.35	3.30
2	35	7011019677	21.2	82.5	57.0	51.0	122	172	312	184	264	60.0	6.35	3.30
2-1/2	55	7011019695	38.6	105	70.0	66.5	145	203	377	238	344	66.5	6.35	6.35
3	* 85	7011019711	56	127	82.5	76.0	165	216	429	279	419	89.0	6.35	6.35

* Individueel beproefd met certificering.

Zadelsluiting Type G-2160



7 through 300 metric tons

400 through 1550 metric tons

G-2160														
Veilige werklust t	Art.nr.	Gewicht kg/st.	Afmetingen mm											
			A	B +/- 6.35	C	D +/- .5	E	G	H	J	K	P	R	
7	7011021256	1,81	105	31.8	17.5	22.4	46.2	31.8	90.4	40.6	31.8	104	149	
12.5	7011021265	4,54	137	42.9	23.4	28.7	60.5	34.8	118	54.1	41.4	140	194	
18	7011021274	6,80	170	51.6	29.5	35.1	68.3	38.1	148	63.5	50.8	172	238	
30	7011021283	11,3	195	60.2	35.1	41.4	88.9	44.5	176	79.5	63.5	216	289	
40	7011021584	20,9	236	73.2	42.9	50.8	102	58.7	205	95.3	76.2	270	346	
55	7011021287	32,2	263	82.6	50.8	57.2	118	66.8	238	114	88.9	311	397	
75	7011021290	45	365	105	53.8	69.9	127	63.5	293	121	92.5	312	468	
400	7011021334	500	769	220	131	160	300	160	575	320	185	690	985	
500	7011021343	650	847	250	146	180	340	170	630	340	225	790	1085	
600	7011021352	860	915	275	158	200	394	185	700	370	247	865	1200	
700	7011021361	1.109	988	300	167	215	376	200	735	400	270	940	1275	
800	7011021254	1.368	1058	325	185	230	420	210	750	420	277	975	1323	
900	7011021389	1.559	1111	350	198	250	430	220	757	440	293	1025	1373	
1.000	7011021370	1.824	1168	380	212	270	450	230	760	460	308	1075	1405	
1.250	7011021272	2.588	1266	430	232	300	533	265	930	530	323	1.175	1.660	
1.550	7011021281	3.650	1394	465	269	320	605	404	1.075	580	338	1.255	1.865	