




Harpsluiting met moerbout
Type G-5263



G-5263													
Veilige werklast t	Art.nr.	Gewicht kg/st	Afmetingen mm										
			A	B	C	D	E	F	G	H	I	J	K
3,3	7020G526333	0.44	13.5	16	34	13	22	51	32	89	82	58	13
5	7020G52635	0.79	16	19	40	16	27	64	43	110	98	75	17
7	7020G52637	1.26	19	22	46	19	31	76	51	129	114	89	19
9,5	7020G526395	1.88	22	25	52	22	36	83	58	144	130	102	22
12,5	7020G5263125	2.78	25	28	59	25	43	95	68	164	150	118	25
15	7020G526315	3.87	28	32	66	28	47	108	75	185	166	131	27
18	7020G526318	5.26	32	35	72	32	51	115	83	201	178	147	30
21	7020G526321	6.94	35	38	80	35	57	133	92	227	197	162	33
30	7020G526330	8.79	38	42	88	38	60	146	99	249	202	175	19
40	7020G526340	15	45	50	103	45	74	178	126	300	249	216	23
55	7020G526355	22	57	57	117	57	83	197	138	341	286	252	26
85	7020G526385	42	70	70	143	70	105	260	180	437	344	320	32
120	7020G5263120	70	83	83	162	83	127	329	190	535	403	356	40
150*	7020G5263150	112	95	95	208	91	147	400	238	647	511	428	50
175*	7020G5263175	160	105	108	238	102	169	410	275	688	561	485	60
* Ronde bout													



Harpsluiting met moerbout
Type G-4263



P-4263													
Veilige werklast t	Art.nr.	Gewicht kg/st	Afmetingen mm										
			A	B	C	D	E	F	G	H	I	J	K
4,75	7020G4263475	2.08	22	25	52	22	63	112	88	173	157	132	23
6,5	7020G426365	3.14	25	28	59	25	75	135	105	204	182	155	25
8,5	7020G426385	4.36	28	32	66	28	82	148	115	225	201	171	28
9,5	7020G426395	5.95	32	35	72	32	90	162	126	248	217	190	31
12	7020G426312	7.87	35	38	79	35	100	180	140	274	240	210	34
16	7020G426316	12.5	38	42	88	38	106	216	159	319	248	325	19
25	7020G426325	18	45	50	103	45	127	248	175	370	296	265	24
30	7020G426330	25	50	57	118	50	146	273	207	411	338	307	27
55	7020G426355	45	65	70	145	65	165	314	213	487	389	343	33
75	7020G426375	70	75	83	166	75	184	330	254	530	432	404	40